

## ステンレス直線

(SUS304)

径	m/kg	2 M	4 M
2.0	0.02		
2.5	0.04		
3.0	0.06		
4.0	0.10		
5.0	0.16		
6.0	0.22		
7.0	0.31		
8.0	0.40		
9.0	0.50		
10.0	0.62		
12.0	0.90		
13.0	1.05		

## ステンレス引抜丸棒

SUS304

径	m/kg
8	0.40
9	0.50
10	0.62
11	0.75
12	0.90
13	1.05
14	1.22
15	1.40
16	1.59
17	1.80
18	2.02
19	2.25
20	2.49
22	3.01
25	3.89
28	4.88
30	5.61
32	6.38
35	7.63
36	8.07
38	8.99
40	9.97
42	10.99
45	12.61

SUS303

径	m/kg
48	14.35
50	15.57
55	18.84
60	22.42
65	26.31
70	30.52
75	35.03
80	39.86

径	m/kg
8	0.40
10	0.62
12	0.90
14	1.22
15	1.40
16	1.59
18	2.02
20	2.49
22	3.01
25	3.89
28	4.88
30	5.61
32	6.38
35	7.63
36	8.07
38	8.99
40	9.97
45	12.61
50	15.57

\* M単重量は参考値です。